



PRODUCT INFORMATION

Our Cork Tiles are a natural, sustainable product that is highly characterful, lightweight and has acoustic properties.

Applications	<ul style="list-style-type: none">- For internal use across a range of sectors including commercial offices, higher education, restaurants, hotels, retail etc.- Can be fastened to curves. Please speak to our Technical Team for details.														
Composition	<ul style="list-style-type: none">- 100% natural cork from oak tree bark, harvested by hand.														
Appearance	<ul style="list-style-type: none">- Highly textural and unique in appearance with varying degrees of tones and nuances - 7 available styles, perfect for a biophilic feature wall within a conscientious design.														
Dimensions	<ul style="list-style-type: none">- Approximately 600mm (width) x 300 mm (height): 600 ± 0.5% 300 ± 0.5%														
Thickness	<ul style="list-style-type: none">- Tile thickness ranges from 3mm - 30mm, depending on the style:<table><tr><td>RAW BARK</td><td>30mm</td></tr><tr><td>FOREST BARK</td><td>26mm</td></tr><tr><td>HEART BLOCK</td><td>8mm</td></tr><tr><td>TAWNY</td><td>3mm</td></tr><tr><td>CLOUD</td><td>3mm</td></tr><tr><td>SNOWDRIFT</td><td>3mm</td></tr><tr><td>DAWN</td><td>3mm</td></tr></table>	RAW BARK	30mm	FOREST BARK	26mm	HEART BLOCK	8mm	TAWNY	3mm	CLOUD	3mm	SNOWDRIFT	3mm	DAWN	3mm
RAW BARK	30mm														
FOREST BARK	26mm														
HEART BLOCK	8mm														
TAWNY	3mm														
CLOUD	3mm														
SNOWDRIFT	3mm														
DAWN	3mm														
Pack Size	<ul style="list-style-type: none">- Pack size varies, depending on the style:<table><tr><td>RAW BARK</td><td>8 tiles</td></tr><tr><td>FOREST BARK</td><td>10 tiles</td></tr><tr><td>HEART BLOCK</td><td>32 tiles</td></tr><tr><td>TAWNY</td><td>11 tiles</td></tr><tr><td>CLOUD</td><td>11 tiles</td></tr><tr><td>SNOWDRIFT</td><td>11 tiles</td></tr><tr><td>DAWN</td><td>11 tiles</td></tr></table>	RAW BARK	8 tiles	FOREST BARK	10 tiles	HEART BLOCK	32 tiles	TAWNY	11 tiles	CLOUD	11 tiles	SNOWDRIFT	11 tiles	DAWN	11 tiles
RAW BARK	8 tiles														
FOREST BARK	10 tiles														
HEART BLOCK	32 tiles														
TAWNY	11 tiles														
CLOUD	11 tiles														
SNOWDRIFT	11 tiles														
DAWN	11 tiles														
Approximate Coverage	<ul style="list-style-type: none">- Approximate coverage shown per pack for each style:<table><tr><td>RAW BARK</td><td>1.44m² / pack</td></tr><tr><td>FOREST BARK</td><td>1.8m² / pack</td></tr><tr><td>HEART BLOCK</td><td>5.76m² / pack</td></tr><tr><td>TAWNY</td><td>1.98m² / pack</td></tr><tr><td>CLOUD</td><td>1.98m² / pack</td></tr><tr><td>SNOWDRIFT</td><td>1.98m² / pack</td></tr><tr><td>DAWN</td><td>1.98m² / pack</td></tr></table>	RAW BARK	1.44m ² / pack	FOREST BARK	1.8m ² / pack	HEART BLOCK	5.76m ² / pack	TAWNY	1.98m ² / pack	CLOUD	1.98m ² / pack	SNOWDRIFT	1.98m ² / pack	DAWN	1.98m ² / pack
RAW BARK	1.44m ² / pack														
FOREST BARK	1.8m ² / pack														
HEART BLOCK	5.76m ² / pack														
TAWNY	1.98m ² / pack														
CLOUD	1.98m ² / pack														
SNOWDRIFT	1.98m ² / pack														
DAWN	1.98m ² / pack														
Water Resistance	<ul style="list-style-type: none">- Not recommended for wet environments.														
Weathering	<ul style="list-style-type: none">- Natural particles allow weathering similar to the original material.														
Installation	<ul style="list-style-type: none">- Vtec Cork tiles are designed to be adhered to a dry, clean smooth surface using the adhesive supplied. Simply follow the installation instructions provided.- Can be applied to a wooden framework or directly to walls.- Acclimatising the tiles to the final room conditions for a minimum of 48 hours prior to installation will ensure best results.- Take care to avoid pressing too hard when adhering to the wall so as not to damage tiles.														





PRODUCT INFORMATION

Natural Materials	- Please note that due to the natural elements used in creating Cork panels, the colours and dimensions can vary between panels and batches, and images of the product are only indicative of the finished product.
Workability	- Cork tiles can easily be cut to shape, as required.
Maintenance	- Cork tiles are easy to preserve and resistant to sunlight. They do not require much maintenance but can benefit from dusting or hovering with a soft brush attachment if needed.

TECHNICAL PROPERTIES

Squareness	- EN 427 600<1.0mm 300<0.5mm
Apparent Density	- Unaffected by temperatures from -30° to 240° C
Dimensional Stability	- D3 to BS 476 : Part 7
Curling	- EN 434 ≤ 6
Moisture Content	- EN 12105 ≤ 7
Thermal Resistance	- EN 12667 0.0572
Fire Resistance	- EN 13501-1 DS1, d0
Sound Absorption	- ISO 354 0.1