



METAL TILES

PRODUCT DATA SHEET

PRODUCT INFORMATION

Our **Metal Tiles** are hand finished to obtain unique patina and colour variations. The real beauty of these tiles is in their imperfections, creating a unique and stunning finish.

Applications	<ul style="list-style-type: none">- For internal use across a range of sectors including commercial offices, higher education, restaurants, hotels, retail etc.
Composition and Finishes	<ul style="list-style-type: none">- Metal tiles in a range of 12 styles of copper, brass, zinc and steel – produced in a gloss finish as standard (matt finish available upon request).- Tiles are hand-finished to obtain unique patina and colour variations, designed to create stunning visuals.- The tiles are coated with a durable polyurethane coating, which gives them UV resistance and anti-corrosion properties.
Sizes	<ul style="list-style-type: none">- Standard sizes are: 240 x 240 mm 260 x 490 mm 490 x 490 mm 490 x 990 mm 190 x 990 mm- Bespoke sizes available upon request.
Thickness	<ul style="list-style-type: none">- Tiles are typically manufactured to a thickness of either 0.5 or 1mm. Copper 0.5mm Brass 0.5mm Zinc 0.5mm Steel 1mm
Approximate Weight	<ul style="list-style-type: none">- Approximate weights vary between 4-8kg, depending on the style: Copper 4.5 kg per m² Brass 4.3 kg per m² Zinc 4 kg per m² Steel 8 kg per m²
Fire Resistance	<ul style="list-style-type: none">- Metal tiles have Inherent Fire Resistance (Class A).
Water Resistance	<ul style="list-style-type: none">- Although the panels are fine in a moist environment, they should not be exposed to regular or direct water (eg. showers, splashbacks). Please contact our Technical Team regarding your application.
Natural Materials	<ul style="list-style-type: none">- These products are manufactured using natural materials and hand finishes; therefore, no two panels are identical. This provides a unique metal look for great visual impact.



METAL TILES

PRODUCT DATA SHEET

PRODUCT INFORMATION

Installation	<ul style="list-style-type: none">- Vtec Metal tiles are designed to be easy and fast to install, perfect to get your interior up and functioning quickly. Full installation instructions are provided.- Store tiles flat, removed from outer packaging, ideally 48 hours prior to installation.- Ensure that the surface the tiles are being attached to are sound and free from dust, grease or any substance that may impede adhesion.- Measure the wall, mark up and apply tiles to the wall using adhesive. Due to the nature of the tiles, care must be taken not to press too hard to avoid the risk of denting or scratching.
Workability	<ul style="list-style-type: none">- Metal tiles can be cut to shape, as required. Take care to protect the tiles and ideally use a cold cutting tool, e.g. electric metal shears, a circular saw with correct cold cutting blade to suit the type of metal of the tiles.
Maintenance	<ul style="list-style-type: none">- Metal tiles may benefit from light dusting, taking care not to scratch the tile surface. They can be wiped with a damp cloth. They can be cleaned with water, and if required add a weak soap solution. Do not use detergent or abrasive cleaners.



Vtec Group Ltd

Head Office and Manufacturing
Unit 3 Cooksland Ind. Estate
Bodmin PL31 2QB

London Showroom
Design Hub Clerkenwell
47 Gee Street, London, EC1V 3RS

T. 03307 00 00 30
E. info@vtecgroupp.co.uk
W. vtecgroupp.co.uk