



MAXIBEAM DATA SHEET







PRODUCT INFORMATION

MaxiBeam is the **lightweight beam system** that provides **visual style** and **acoustic absorption** simply (if required), alongside being easy to specify and fast to install.

Applications



- For internal use across a range of sectors including commercial offices, higher education, restaurants, hotels, retail etc.
- Versatile system suitable for walls, ceilings, rafts or independent screens.

Composition



- Lightweight hollow-core construction with rigid outer surfaces using our specialist VFR core material.
 This specialist method and materials ensure the beam is more dimensionally stable. i.e. It will not warp and twist like solid timber.
- FR Laminate finish and matching edging to all visible surfaces.
- Premium grade EchoTone Acoustic Backing Board can be incorporated with the MaxiBeams.

Standard Sizes and Weights

HEIGHT / DEPTH 100mm 125mm 150mm 200mm 285mm 50mm 50mm 50mm 50mm 50mm APPROX. WEIGHT 3.1kg/per lm 3.5kg/per Im 3.9kg/per lm 5.1kg/per lm 6.3kg/per lm Beams are installed individually so the spacing is fully customizable, including random / varied spacings between beams. TYPICAL GAP / SPACE BETWEEN THE BEAMS As a general rule of thumb, the minimum space between beams is the beam height and the maximum space between is 3x the beam height. Please note that some projects have had smaller or larger spacings than this rule of thumb.

- 200mm is the recommended minimum beam depth for vertical screens.
- MaxiBeam is typically manufactured to size for the project. Maximum lengths of 2980mm are possible, and where longer runs are required discreet End-To-End joiners are used.
- The most efficient lengths for production are 2980mm, 1480mm & 980mm.
- Bespoke options can be manufactured including:
- Thickness's
- Heights
- Lengths
- Geometric & Angular Shapes
- Angled Ends



MAXIBEAM








PRODUCT INFORMATION

Beam End Options


SOUARE END - NO JOINER








MITRED CORNERS OR BESPOKE ANGLED CONNECTIONS





Acoustics



- MaxiBeam is frequently installed with our Acoustic Backing Board to achieve good levels of acoustic absorption.
- Budapest Black is available in 9mm or 12mm thickness. All other colours are 12mm thick. (See pg 4 for colour options)
- Acoustic Absorption varies according to MaxiBeam centres, heights, and void depth behind the Beams.

 Please speak to our Technical team for details and acoustic test data.

Beam Finishes

- SUPALAMI A range of high quality, realistic, economic and hard-wearing laminate finishes.
- Bespoke options available on request.

Fire Performance



SUPALAMI - FR Euroclass B rating is available - please contact us for test certificates.

Sustainability Certification



- We are FSC® certified (FSC® C160047)
- MaxiBeam is available as FSC® Certified. Please talk to us about your specific requirements prior to quotation or specification.

Natural Materials

- Although MaxiBeam is renowned for its stability with our production methods and processes, panels are produced using natural products. Therefore, we cannot accept responsibility for pieces that warp, twist, expand, contract, move etc.
- Changes to temperature and humidity can also have an impact.

MAXIBEAM





PRODUCT INFORMATION

Access and Service Integration



- The MaxiBeam system integrates well with access and service requirements, such as:
- Access hatches at specific locations
- Hidden doorways
- Lighting
- HVAC grilles
- Smoke detectors and sprinklers
- AV screens and cabling
- It can also be fully removable for access to the void.

Installation - Walls, Ceilings and Rafts

 Supplied as individual beams, fully finished to avoid on-site cutting, which are then discreetly installed. Beams can be installed so they are removable if required.

- The MaxiBeam system can be fastened to almost any type of common substrate.

Ceiling Rafts and Walls

Fixing Cleat

Screw from Rear

Click-Fix (Removable)

Installation - Screens



- _ Vertical screens can be:
 - Vertical slats
 - Horizontal slats
 - Angled and louvred slats
 - Combination of the above
- MaxiBeam screens can be fastened to almost any common ceiling or floor.
- Screen installation method will depend on the construction it is fastened to and if it needs to be removable.

Workability

- Beams can be joined on site using discreet, machined push-fit joiner. If beams do require cutting, use standard woodworking tools.

Antimicrobial Finish

- Our standard range of Supalami laminated finishes have been tested successfully to ISO 22196:2011, providing you with a great looking, cost-effective finish that can support better hygiene in your chosen space (only when MaxiBeam is used with a Supalami finish).
- Recognised worldwide, this test provides the highest standard of antibacterial testing available and
 measures the reduction over 24 hours of Staphylococcus Aureus and E-Coli bacteria, and the effectiveness of the antibacterial properties on the surface. All of the standard finishes scored > 3 which is
 the highest possible classification, confirming that the surfaces have a strong antibacterial effect.
 Please advise us before quoting if you require antimicrobial coating.

Maintenance

No maintenance needed apart from occasional dusting. Any dirt deposits can be wiped off.
 Beams should not be subjected to moisture or wet cloths.



MAXIBEAM





ACOUSTIC BACKING COLOUR SWATCHES

OUR MOST POPULAR ACOUSTIC BACKING COLOUR - BUDAPEST BLACK





ROTTERDAM RED



RICHMOND RED



ONTARIO ORANGE



OAKLAND ORANGE



PANAMA PINK



YORKTOWN YELLOW



YOKOHAMA YELLOW



BOSTON BROWN



GENEVA GREEN



GIBRALTAR GREEN



GRENADA GREEN



TORONTO TEAL



TOKYO TEAL



BOLOGNA BLUE



BALTIMORE BLUE



BARCELONA BLUE



PALERMO PURPLE



BROOKLYN BEIGE



BERLIN BEIGE



BOGOTÁ BEIGE



GLASGOW GREY



GENOA GREY



GRENOBLE GREY



GUADELOUPE GREY



WARSAW WHITE



Page 4

Issue 6: May 2024