



MAKING  
SPACES  
MATTER

TEXTURE PANEL SYSTEM

# BRICK

## DATA SHEET

VTECGROUP.CO.UK

03307 00 00 30 | sales@vtecgroup.co.uk

# BRICK

## PRODUCT DATA SHEET



### PRODUCT INFORMATION

#### Applications



- For internal use across a range of sectors including commercial offices, higher education, restaurants, hotels, retail etc.
- Suitable for walls, ceilings and curves (please consult us for radii below 4 metres).

#### Composition



- Natural pigments and oxides form the outer surface of the reinforced polyester matrix.
- Produced from original brick wall.
- **8 standard designs:**

LONDON BRICK MULTI	LONDON BRICK RED
LONDON BRICK AGED RED	LONDON BRICK WHITE
LONDON BRICK SANDY BROWN	LONDON BRICK DISTRESSED WHITE
LONDON BRICK DARK GREY	LONDON BRICK AGED WHITE

#### Dimensions

- Nominal sheet size is 3.29m (width) x 1.27m (height).

#### Thickness

- Approximately 5mm thick and they take on the relief of the original brick wall, of which will typically be a maximum of 15mm.

#### Weight

- Approximately 8.14 kg/m<sup>2</sup>

#### Water Resistance

- Unaffected by moisture, water resistant.

#### Weathering

- Natural particles allow weathering similar to the original material.

#### Natural Materials

- Please note that due to the natural elements used in creating London Brick panels, the colours and dimensions can vary between panels and batches, and images of the product are only indicative of the finished product.

#### Installation

- Easily through-fixed to substructure or walls. Substructure can be a framework of aluminium or wood, or to walls of masonry or timber board walls. Joints and fixings are disguised during installation with homogeneous system. Large panel size means they are quick to install compared to more traditional methods.


#### Workability

- Cut with diamond abrasive wheels, TCT blades in a jigsaw or water jetting.

#### Maintenance

- No maintenance apart from occasional dusting. Any dirt deposits can be wiped off.

PRODUCT  
INFORMATIONTECHNICAL  
PROPERTIES

Density	- Average 1700 kg/m <sup>3</sup>
UV Resistance	- Excellent
Temperature Resistance	- Unaffected by temperatures from -30° to 240° C
Fire Resistance 	- D3 to BS 476 : Part 7 (FR version also available to Euroclass B-S3,d0)
Thermal Conductivity	- K-value = 0.23 w/m <sup>2</sup> °C
Thermal Expansion	- 30 x 10 <sup>-6</sup> mm/°C
Impact Resistance	- 19844j/m <sup>2</sup> to UNE 150 179