



MICROSLAT DATA SHEET

VTECGROUP.CO.UK

03307 00 00 30 | sales@vtecgroup.co.uk





MICROSLAT PRODUCT DATA SHEET



PRODUCT **INFORMATION**

Our MicroSlat range is a modular slatted panel system that offers the visual appeal of wooden slats with cost-effective finishing options, rapid installation and acoustic performance.

Applications	 For internal use across a range of sectors including commercial offices, higher education, restaurants, hotels, retail etc. Versatile system suitable for walls, ceilings or rafts. 							
Composition	 High quality slat, manufactured from our VFR Grey Core material. Finished with our premium Supalami laminate finish to the face of the slat. Premium grade Acoustic Backing integrated behind the slats. Safe, non-toxic, non-irritant. 							
	- Choose from 11 standard MicroSlat sizes (dimensions below in mm):							
	Product Name	Slat Width	Gap	Centres	Approx Weight m² (Budapest Black 9mm PET)	Approx Weight m² (Coloured 12mm PET)	% Open Area	
Slat Sizes, Spacings and Approx. Weight	MicroSlat 30-10	30	10	40	15.4	15.8	25%	
	MicroSlat 30-45	30	45	75	9.2	9.7	60%	
	MicroSlat 30-70	30	70	100	7.4	7.9	70%	
	MicroSlat 50-16	50	16.67	66.67	15.4	15.8	24%	
	MicroSlat 50-25	50	25	75	13.9	14.4	33%	
	MicroSlat 50-70	50	70	120	9.5	10.0	58%	
	MicroSlat 50-100	50	100	150	8.0	8.5	67%	
	MicroSlat 70-16	70	15.71	85.71	16.6	17.0	19%	
	MicroSlat 70-30	70	30	100	14.5	15.0	30%	
	MicroSlat 70-50	70	50	120	12.5	12.9	42%	
	MicroSlat 70-80	70	80	150	10.4	10.8	53%	
Panel Size	Standard panel size is (mm): - 3000 (h) x 600 (w). Bespoke sizes are available upon request.							
Panel Thickness	- Budapest Black Acoustic Backing = nominal 23mm thick (14mm thick slat + 9mm thick backing)							
	- Coloured Acoustic Backing = nominal 26mm thick (14mm thick slat + 12mm thick backing).							
Slat Finishes	- SUPALAMI High quality, realistic, economic and hard-wearing laminate finish.							
Slat Core Colour	- VFR Grey Core is a grey colour throughout. The exposed slat edges show the VFR Grey Core colour.							
Fire Performance	- FR Grade - Euroclass B Rated. Contact us for test data.							



Vtec Group Ltd

Head Office and Manufacturing Unit 3 Cooksland Ind. Estate Bodmin PL31 2QB

T. 03307 00 00 30 E. info@vtecgroup.co.uk W. vtecgroup.co.uk

Issue 6: August 2024 Page 1

MICROSLAT

PRODUCT INFORMATION

Sustainability Certification	- MicroSlat is FSC [®] Certified (FSC [®] C160047)
Acoustics	 MicroSlat panels are backed with Acoustic Backing Board to help absorb unwanted reverberation. Acoustic Absorption varies according to slat sizes, slat spacings, void depth and if further insulation is used. For improved acoustic performance, create an air gap behind the panel, and for even further improvement add rockwool insulation. Please speak to our Technical team for details and acoustic test data.
Acoustic Backing Colour	 Budapest Black Acoustic Backing - 9mm thickness Or choose from 25 beautiful colours (see next page) - 12mm thick. Please note that the coloured acoustic backing is 2400mm in length. Therefore for MicroSlat 3000mm panels there is a butt join on the acoustic backing. The slats are manufactured as 3000mm lengths.
Natural Materials	 Although MicroSlat is renowned for its stability with our production methods and processes, panels are produced using natural products. Therefore, we cannot accept responsibility for pieces that may show warping, twisting etc. Please note that the slats will absorb or lose moisture depending on the surrounding environment, which means they can expand, contract, warp and move etc. over time in relation to the moisture changes.
Access and Service Integration	 The MicroSlat system integrates well with access and service requirements, such as: Access hatches at specific locations Hidden doorways Lighting HVAC grilles Smoke detectors and sprinklers AV screens and cabling
Modular System	 Speak to our Technical team if removable panels are required for access to behind. Supplied as modular panels, fully finished, which are then discreetly installed. Panels are easy to cut on site if needed. Panels can also be installed so they are removable if required.
Substrate Options	 The MicroSlat system can be fastened to almost any type of common substrate: Direct to plaster-boarded walls or ceilings (good acoustic performance) With 50mm air gap (improved acoustic performance) With 50mm air gap & rockwall insulation (best acoustic performance) Speak to our Technical Team for further acoustic test data and information.
Installation	 SCREW FIX Panels can be screw fixed to walls or ceilings (substrates outlined above). The screws can be colour coordinated to the acoustic backing colour.
Workability	 MicroSlat panels are supplied fully finished and delivered ready to fit, with full installation instructions. They are easy to work with and adapt on site. If panels do require cutting, use standard woodworking tools.
Maintenance	 No maintenance needed apart from occasional dusting. Any dirt deposits can be wiped off. Panels should not be subjected to moisture or wet cloths.



Vtec Group Ltd

Head Office and Manufacturing Unit 3 Cooksland Ind. Estate Bodmin PL31 2QB

T. 03307 00 00 30 E. info@vtecgroup.co.uk W. vtecgroup.co.uk Issue 6: August 2024 Page 2

MICROSLAT

ACOUSTIC BACKING COLOUR SWATCHES

OUR MOST POPULAR ACOUSTIC BACKING COLOUR - BUDAPEST BLACK



ROTTERDAM RED	RICHMOND RED	ONTARIO ORANGE	OAKLAND ORANGE	PANAMA PINK
YORKTOWN YELLOW	YOKOHAMA YELLOW	BOSTON BROWN	GENEVA GREEN	GIBRALTAR GREEN
GRENADA GREEN	TORONTO TEAL	TOKYO TEAL	BOLOGNA BLUE	BALTIMORE BLUE
BARCELONA BLUE	PALERMO PURPLE	BROOKLYN BEIGE	BERLIN BEIGE	BOGOTÁ BEIGE
GLASGOW GREY	GENOA GREY	GRENOBLE GREY	GUADELOUPE GREY	WARSAW WHITE



Head Office and Manufacturing Unit 3 Cooksland Ind. Estate Bodmin PL31 2QB

T. 03307 00 00 30 E. info@vtecgroup.co.uk W. vtecgroup.co.uk Issue 6: August 2024

Page 3